

VehiclePro Prewash RM 803 Classic

VehiclePro PreWash RM 803 Classic: Powerful yet gentle high-pressure pre-spraying agent. Accelerates the softening and removal of oils and greases, as well as insect residues.

pH value 12
in concentrate



Properties

- Effective pre-spraying agent for prewashing cars and commercial vehicles
- Expands and reliably loosens grease, oil, dirt caused by emissions, and insects
- This means the cleaning result of subsequent cleaning steps is significantly improved
- Cleaning action in all temperature ranges
- Rapidly effective
- Gentle on materials
- Tensides biodegradable in accordance with EEC 648/2004
- Quick oil and water separation in the oil separator (easily separable = asf)
- NTA-free

Usage options

- High-pressure cleaners
- Car washes
- Self-service washing stations
- Spray units

Application areas

Car dealership and garage	Car de-waxing, Vehicle cleaning
Municipal	Car/engine wash
Haulage contractors, bus operators	Vehicle cleaning, Car/engine wash
Self-service washing stations	Cars, commercial vehicles, bicycles

Technical data

Container sizes	Packaging unit	Part number
10 l	1 Piece(s)	6.296-061.0
20 l	1 Piece(s)	6.296-062.0
200 l	1 Piece(s)	6.296-063.0

Application

High-pressure cleaners

- Apply primary mixture with fresh water.
- Set the dosage and temperature on the device
- Clean object.
- Rinse surface well with clear water.

Car washes

- Insert the product into the system.
- Adjust dosage on the device.
- Clean object.
- Then run through washing programme.

Self-service washing station

- Insert the product into the system.
- Adjust dosage on the device.
- Clean object.
- Rinse surface well with clear water.

Spray unit

- Combine the product with the appropriate dosage and fresh water.
- Wet object completely with the product.
- Allow to soak.
- Contact time 1-5 minutes, depending on the degree of soiling.
- Rinse surface well with clear water.

Instructions for use

- Test on an inconspicuous part for material compatibility.
- Do not let the cleaning solution dry out.
- Store away from frost.

Warnings and safety recommendations according to EC Directives

- Danger
- H290 May be corrosive to metals
- H314 Causes severe skin burns and eye damage
- P280 Wear protective gloves/protective clothing/eye protection/face protection.
- P305 + P351 + P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
- P303 + P361 + P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water [or shower].
- P310 Immediately call a POISON CENTER/doctor.
- P405 Store locked up.
- P501a Dispose of contents/container in accordance with local/regional/national/international regulations.

Further information

- Material Safety Data Sheet (MSDS)

Dosage and yield

Contents	Cleaning method	Primary mixture	Dosage	Soiling	Yield
1000 ml	High-pressure cleaners	1+2	1.5 - 6 %	strong	200 m ²
1000 ml	Vehicle wash system		0.5 - 2 %	strong	100 Car
1000 ml	Self-service washing stations	1+2	1.5 - 6 %	strong	36 Car
1000 ml	Spray units		2 %	medium-strong	550 m ²